

## DIGITAL SIGNAL PROCESSOR WITH PARALLEL ARCHITECTURE

### Field of the Invention

The present invention relates to digital signal processors (DSPs), and more particularly, to a DSP with a parallel architecture or a VLIW (very large instruction word) processor.

### Background of the Invention

As is well known to those skilled in the art, VLIW type processors are processors derived from RISC (reduced instruction set computer) processors which differ from conventional DSPs in that they comprise several parallel-mounted execution units. Each execution unit is the equivalent of a RISC processor core and executes instruction codes in reduced format, generally 16-bit codes, by exploiting the resources offered by a bank of registers. Since each execution unit is capable of carrying out an instruction code simultaneously with the other execution units, the VLIW processors are therefore capable of simultaneously executing a large instruction comprising several RISC equivalent codes in parallel.

To give a better understanding, Figure 1 presents a schematic view of the standard structure of a VLIW type processor 10 whose essential elements are shown in block form. The processor 10 comprises a program memory PMEM, a data memory DMEM, an instruction register IR positioned at the output of the memory

PMEM, an instruction decoder IDEC positioned at the output of the register IR, a bank of registers REGBANK designed to execute the RISC type instruction codes, execution units EU0 to EU3, as well as a circuit BMC  
5 forming the interface between the execution units UE1-EU3 and the inputs/outputs of the data memory DMEM. The execution units, which herein are four units EU0, EU1, EU2, EU3, are parallel-connected to simultaneously process four instruction codes that are read  
10 simultaneously in the memory PMEM, together forming a large instruction. The nature of the execution units may vary as a function of the application for which the processor is designed. The execution units comprise for example an ALU (arithmetic and logic unit), a MAC  
15 (multiplication/addition) unit, a CU (control unit managing the program counter PC and the connections), and a CO-PRO (coprocessor) unit to perform certain computations specific to the application.

A processor of this kind is thus capable of  
20 executing large instructions which herein includes at most four codes. At each new clock cycle H, the program counter PC of the processor is increased by an increment n which is equal to 1, except in the case of a jump or a call, and the instruction registers IR0-IR3  
25 receive four new codes simultaneously and in parallel. These four new codes are to be executed by the units EU0-EU3.

The architecture of a processor 10 of this kind thus differs from a conventional RISC processor by  
30 its parallelism which can be found at all stages in the processing of the instructions. However, the possibilities offered by this parallelism are rarely exploited to the maximum, and the compiled programs stored in the program memory PMEM generally comprise a  
35 large number of no-operation or NOP codes. Indeed, the conversion of a program written in a high-level language, for example the language C/C++, into a

sequence of RISC type codes combined in bundles is done automatically by a compilation program that knows the structure of the processor and tries to form bundles of the largest possible size (with a maximum of four codes in the exemplary processor being described) to exploit the parallelism of the processor to the maximum. This optimization is done by taking account of the conflicts between the codes, the availability of the execution units and the data dependence during the pipeline execution of the codes. Thus, for example, two codes designed to be executed by the same execution unit cannot be executed in parallel in the same bundle. Equally, a code using an operand that is the result of an operation that is object of another code cannot be executed so long as the code on which it depends is not itself executed.

For example, let us consider the following program sequence:

/p c0	/p c1	p c2	/p c3	p c4	p c5	p c6	/p c7	p c8	p c9
-------	-------	------	-------	------	------	------	-------	------	------

which comprises instruction codes c0 to c9 comprising a parallelism bit /p or p. The instruction codes, known to those skilled in the art as syllables, are put together in bundles to form large instructions. The separation of the instructions (bundles) within a program is done by the parallelism bits p assigned to each of the codes. The two possible values /p or p of a parallelism bit, for example 0 and 1, tells whether or not the code belongs to a new instruction. More particularly, a code preceded by a parallelism bit p (for example 1) belongs to the same instruction as the previous code, while a code preceded by a parallelism bit /p (for example 0) belongs by convention to a new bundle.

In the program sequence mentioned above, the parallelism bits are thus used to distinguish four large instructions INST1 to INST4:

INST1 = c0

5 INST2 = c1 c2

INST3 = c3 c4 c5 c6

INST4 = c7 c8 c9

So that they can be executed by the processor 10, these instructions INST1 to INST4 are recorded in the program memory PMEM of the processor as shown in Figure 1 and described in the following Table 1:

TABLE 1

	/p c0	NOP	NOP	NOP
	/p c1	NOP	NOP	NOP
15	/p c3	p c4	p c5	p c6
	/p c7	p c8	p c9	NOP

Consequently, the compilers for standard VLIW processors generate a large number of no-operation codes for keeping certain execution units inactive while others execute codes. This may result in the program memory becoming over-burdened with 20% to 70% of the memory space being taken up, depending on the efficiency of the compiler and the matching between the program to be compiled and the resources offered by the processor. This over-burdening of the memory space by NOP codes, which is considerable in relation to the instruction programs really needed for the execution of the programs, increases the surface of the memory PMEM for a given application. This therefore causes a drop in performance (the memory is slower with the increase in size), additional consumption (the word lines and bit lines are longer in the memory array) and costs (in terms of silicon surface area).

Summary of the Invention

In view of the foregoing background, an object of the present invention is to overcome the above described drawbacks. More particularly, the  
5 object of the present invention is to provide a VLIW type processor capable of receiving, in its program memory, bundles of codes that do not comprise any no-operation codes.

These objects, features and advantages are  
10 provided by a signal processor designed to execute variable-sized instructions that may comprise up to N elementary instruction codes. The processor comprises a memory program comprising I individually addressable, parallel-connected memory banks, with I being at least  
15 equal to N, and wherein the codes of a program are recorded in an interlaced fashion at the rate of one code per bank and per address applied to the bank. The processor further comprises means for reading the program memory arranged to read a code in each of the I  
20 memory banks during a cycle for reading an instruction. A cycle for reading an instruction in the program memory comprises reading a sequence of codes that comprises the instruction code or codes to be read and can also, when the number of codes of the instruction  
25 read is smaller than I, comprise codes belonging to a following instruction.

According to one embodiment, the read means comprises means for the application, to the memory banks, of the individual addresses generated from a  
30 collective value of a program counter that is incremented by a value equal to the number of codes comprising the previous instruction before the beginning of a cycle for reading an instruction.

According to another embodiment, the means to  
35 apply addresses apply, to each of the memory banks, an individual read address equal to P0 or P0+1, with P0

being the quotient of the division by I of the value of the program counter.

According to another embodiment, the means for applying the addresses applies to an i ranking memory bank an address equal to P0 when i is strictly greater than R, or for the applying to an i ranking memory bank an address equal to P0+1 when i less than or equal to R, with R being the remainder of the division by I of the value of the program counter.

10 According to yet another embodiment, the read means comprises means for reorganizing the codes of the sequence of codes read in the program memory, according to the following algorithm:  $c'(j) = c(i)$ , with  $i = (j+R') \text{ modulo } I$ , in which i and j designate the ranks of the codes before and after reorganization, c(i) designates i ranking codes in their arrangement after reading in the memory, c'(j) designates j ranking codes after reorganization, and R' is the remainder of the division by I of the value that was shown by the  
15 program counter during the previous clock cycle.

20 According to another embodiment, the means for reorganizing are arranged for the application to the sequence of codes read in the program memory of a circular permutation comprising a number of elementary  
25 circular permutations equal to R' or to I-R' depending on the direction in which the circular permutation is made.

According to yet another embodiment, the circular permutations are performed by a barrel shifter  
30 receiving the parameter R' at a control input.

Advantageously, the read means comprises means to filter the codes that do not belong to the instruction to be read, using parallelism bits accompanying the codes.

35 According to another embodiment, the filtered codes are replaced by no-operation codes.

According to one embodiment, the code-filtering means are arranged to execute the following algorithm: For  $j = 0$ ,  $\text{val}(j=0) = v$ ,  $s(j=0) = c'(j=0)$ ; For  $j$  going from 1 to  $I$ ,  $\text{val}(j) = v$  if  $\text{val}(j-1) = v$  and  
5 if parallelism bit of  $c'(j) = p$ , else  $\text{val}(j-1) = /v$ ;  
 $s(j) = c'(j)$  if  $\text{val}(j) = v$ ;  $s(j) = \text{NOP}$  if  $\text{val}(j) = /v$ ,  
in which  $\text{val}(j)$  is a validation term associated with  
each  $j$  ranking code,  $c'(j)$  is capable of having two  
values  $v$  and  $/v$ ,  $s(j)$  designates  $j$  ranking outputs of  
10 the filtering means corresponding to same ranking  
inputs receiving a code  $c'(j)$ , and NOP is a no-operation code.

According to another embodiment, the non-filtered codes are sent to parallel-mounted RISC type  
15 execution units.

The present invention also relates to a method for the reading of variable-sized instructions that may include up to  $N$  elementary instruction codes, applicable to a signal processor. The method comprises  
20 the steps of providing for a program memory comprising  $I$  individually addressable parallel-connected memory banks, with  $I$  being at least equal to  $N$ . The method further includes recording the codes of a program in the program memory in interlaced fashion, at a rate of  
25 one code per bank and per address applied to the bank. During a read cycle of an instruction, the method includes reading a sequence of codes in the  $I$  memory banks. The said sequence comprises the code or codes of the instruction to be read and possibly also  
30 comprises, when the number of instructions codes read is smaller than  $I$ , with the codes belonging to a following instruction.

According to yet another embodiment, the method comprises the application, to the memory banks,  
35 of the individual addresses generated from a collective value of a program counter, that is incremented by a value equal to the number of codes contained in the

previous instruction before the beginning of a cycle for reading an instruction.

According to another embodiment, the method comprises the application, to each to the memory banks, of an individual read address equal to  $P0$  or  $P0+1$ , with  $P0$  being the quotient of the division by  $I$  of the value of the program counter. An  $i$  ranking memory bank receives an address equal to  $P0$  when  $i$  is strictly greater than  $R$  or an address equal to  $P0+1$  when  $i$  is smaller than or equal to  $R$ , with  $R$  being the remainder of the division by  $I$  of the value of the program counter.

According to another embodiment, the method comprises the reorganization of the codes of the sequence of codes read in the program memory, according to the algorithm mentioned above.

According to yet another embodiment, the method comprises a step of filtering the codes read, that do not belong to the instruction to be read, using parallelism bits accompanying the codes.

According to another embodiment, filtered codes are replaced by no-operation codes.

According to another embodiment, the codes are filtered according to the algorithm mentioned above.

According to yet a further embodiment, the non-filtered codes are sent to parallel-connected RISC type execution units.

#### **Brief Description of the Drawings**

These objects, features and advantages as well as others of the present invention shall be explained in greater detail in the following description of an exemplary embodiment of a processor according to the invention, given by way of a non-restrictive description with reference to the appended figures, of which:



Figure 1, is a block diagram of the architecture of a standard VLIW processor, according to the prior art;

Figure 2 is a block diagram of the blocks of the architecture of a processor according to the present invention; and

Figures 3 and 4 respectively illustrate detailed embodiments of selected elements represented in Figure 2.

#### 10      Detailed Description of the Preferred Embodiments

Figure 2 is a schematic view of the architecture of a signal processor 20 according to the invention. The processor 20, like the standard processor of Figure 1, has a program memory PMEM1, a data memory DMEM, an instruction register IR, an instruction decoder IDEC positioned at the output of the register IR, a register bank RBANK, execution units, in this case four units EU0 to EU3. The processor 20 further includes a BMC (built-in self-test/mapping/conflicts) circuit designed to read or write data elements in the data memory DMEM or in the register bank RBANK, and to fulfil various other functions such as the built-in self-test (BIST) function and the management of address conflicts. The instruction register IR comprises four parallel-connected registers IR0 to IR3 designed for the reception, at each instruction reading cycle (or fetch cycle), of four instruction codes c'(0) to c'(3) delivered by the program memory PMEM1. The instruction decoder IDEC decodes the codes c'(0)-c'(3) as well as distributes the operands to the execution units concerned. These elements are standard and form the core of the processor schematically shown in block form.

35      The processor 20 according to the invention differs from a standard processor in that the program

memory PMEM1 includes several parallel-connected memory banks, in this case four individually addressable banks M0, M1, M2, M3 that respectively receive addresses a0, a1, a2, a3. Hereinafter, the reference I designates the number of individually addressable memory banks present in a processor according to the invention, N designates the maximum number of instruction codes that may be contained in a large instruction (bundle) and, I is at least equal to N. In the illustrated example, I is equal to N which is equal to 4 since the processor comprises four execution units.

According to the invention, the instruction codes (syllables) of a program are recorded in a memory PMEM1 in an interlaced fashion, in such a way that two codes succeeding each other in the program are arranged in two contiguous memory banks of increasing rank with the same address  $a_i$  in each bank. When a code is registered in the last memory bank M3, at an address  $a_3 = x$ , the next code is registered in the memory bank M0 at the address  $a_0 = x+1$ , and the following codes are registered in the banks M1, M2, M3 at the addresses  $a_1 = a_2 = a_3 = x+1$ , etc.

To provide a better illustration of the present invention, we shall assume that the following program of sequences, already described in the introduction, is stored in the virtual memory PMEM1:

INST1 = c0  
INST2 = c1 c2  
INST3 = c3 c4 c5 c6  
INST4 = c7 c8 c9

Unlike a standard processor, the codes forming the large instructions INST1 to INST4 are recorded in the memory banks one after the other without any injection of no-operation codes NOP as can be seen in the Table 2 below. The separation of the instructions is provided exclusively by the parallelism bits.

TABLE 2

Addresses	Bank M0	Bank M1	Bank M2	Bank M3
X	/p c0	/p c1	p c2	/p c3
x+1	p c4	p c5	p c6	/p c7
x+2	p c8	p c9	/p...	...

It may be noted here that the parallelism bits are represented herein as elements external to the codes c0 to c9 to facilitate the understanding of the invention. In practice, the parallelism bits form an integral part of the codes stored in the memory and are eliminated at the time of the execution of the codes. For example, the codes c0-c9 comprise 16 bits, among which one bit is used as a parallelism bit.

Thus, advantageously, the processor according to the invention receives compact programs that do not comprise any NOP codes. The result thereof is a substantial reduction of the amount of memory space required. This results in a reduction of the surface area needed for the storage of the program and a reduction of consumption.

A description shall now be given for reading the memory PMEM1, designed to disinterlace the instruction codes in order to extract therefrom the large instructions or bundles, comprising several codes or syllables designed to be executed simultaneously.

According to the invention, these read means essentially comprise an address management circuit IAC, a code permutation circuit PCC, and a code selection circuit CSC and includes a special mode of management for the program counter PC of the processor 20 which shall be described first of all.

The program counter PC is incremented conventionally at each clock cycle, for example by an adder ADD1 receiving the current value of the program

counter at one input and an increment  $n$  at another input. The output of the adder is applied to a buffer LT1 driven by the clock signal  $H$ . According to the invention, the program counter  $PC$  is incremented by a value  $n$  which is not constant as in the prior art. The increment  $n$  is equal to the number of executable instruction codes contained in the previous instruction and is delivered by the circuit  $CSC$  described below.

This rule of incrementation of the program counter relates naturally to the sequential reading of the instructions of a program and cannot be applied during the execution of special instructions such as jump or call instructions for which the jump increment or the call value is dictated by the program.

The address management circuit  $IAC$  computes the individual addresses  $a_0$ - $a_3$  applied to the memory banks from the current value of the program counter  $PC$ , incremented in the manner that has just been described. More particularly, the circuit  $IAC$  computes the addresses  $a_0$ - $a_3$  by applying the following algorithm  $A1$ :

$A1$ : for  $i$  ranging from 0 to  $I-1$ ,

$a_i = P0+1$  if  $i < R$

$a_i = P0$  if  $i = R$

where:

- 1)  $i$  is the index designating the rank of the memory banks  $M_0$ - $M_3$  and the rank of the corresponding addresses  $a_0$ - $a_3$ ;
- 2)  $P0$  is the quotient of the division by  $I$  of the program counter  $PC$ , giving:

$$P0 = \text{Quotient } (PC/I)$$

namely in this case  $I$  is equal to 4:

$$P0 = \text{Quotient } (PC/4)$$

3) R is the remainder of the division by I of the program counter PC, giving:

$$R = PC - P0 = PC \text{ modulo } I,$$

namely, in this case, I is equal to 4:

5  $R = PC \text{ modulo } 4$

13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211

As shown in Figure 2, the circuit PCC may be made by a conventional type barrel shifter. The algorithm A2 is implemented by the application to the control input of the barrel by a buffer LT2, of the parameter R computed and delivered by the circuit IAC. Since the buffer LT2 is driven by the clock signal, the parameter R that is applied to the barrel shifter after each leading edge of the clock signal is shifted by a clock signal with reference to the parameter R of the cycle in progress, and is therefore equal to the parameter R'. The barrel shifter PCC is positioned to shift its outputs in relation to its inputs by leftward circular permutation (in the direction going from the most significant values to the least significant values), and by performing a number of leftward shifts equal to R'. In one alternative embodiment, the barrel shifter receives at its control input the complement of R' at I, namely the value [I-R'], and is laid out so as to shift its outputs in relation to its inputs by rightward circular permutation (in the direction going from the least significant values to the most significant values) by performing a number of rightward shifts equal to [I-R'].

The code-selection circuit CSC mentioned above is connected at its input to the output of the circuit PCC and comprises inputs e0 to e3 respectively receiving the codes c'(0) to c'(3). The circuit CSC also comprises four outputs s0 to s3 that copy the code received at the same ranking input in conditions set by the following algorithm A3:

```

A3: for j = 0
    val(j=0) = v
    s(j=0) = c'(j=0)
    for j ranging from 1 to I
35  val(j) = v
    if val(j-1) = v

```

```

and if parallelism bit of c'(j)= p
else val(j-1) = /v
s(j) = c'(j) if val(j) = v,
s(j) = NOP if val(j) = /v

```

- 5 where val(j) is a daisy chain type of recursive validation term associated with each j ranking output s(j) that can have two values v and /v, for example 1 and 0. For the j ranking outputs ranging from 1 to I, this term can be used to determine whether an output
- 10 s(j) must copy the code c'(j) received at the corresponding ranking input or, on the contrary, deliver a NOP code. This choice is a function of the value of the validation term val(j) which itself is a function of the value of the preceding validation term
- 15 val(j-1) and of the value p or /p, for example 1 or 0, of the parallelism bit present in the code c'(j).

- In other words, assigning, by convention, the value 1 to p and v and the value 0 to /p and /v, the output s0 copies the code c'(0) received at the input
- 20 e0 and each of the other outputs s(j) copies the code c'(j) received at the corresponding input e(j) if the code c'(j) comprises a parallelism bit equal to 1, and if the validation bit val(j-1) of the previous ranking output is also equal to 1. When the parallelism bit of
- 25 a code c'(j) is equal to 0, the corresponding output s(j) and all the following outputs deliver a NOP code.

The system for reading the program memory PMEM1 thus works as follows:

- Step E1: during a first clock cycle, the
- 30 circuit IAC applies addresses a0-a3 to the memory banks M0-M3, providing for the reading of four instruction codes a(0)-a(3) which follow each other in the memory PMEM1 according to the interlacing described above.

- Step E2-1: during the following clock cycle,
- 35 a read signal READ is applied to the memory banks and the codes are read in an order which, because of their

interlacing, cannot correspond to their effective rank planned in the program. They are rearranged in order by the circuit PCC applying the algorithm A2 by the parameter R' computed in a previous clock cycle (where  
5 the addresses a0-a3 were prepared).

Step E2-2: during the same clock cycles, the selection circuit CSC identifies the codes that do not correspond to the instruction to be executed, by means of their parallelism bit /p and replaces them with no-  
10 operation codes NOP.

Step E2-3: during the same clock cycle, the instructions register IR0 receives the code c'(0) and the registers IR1-IR3 receive the filtered codes (NOP) or non-filtered codes depending on the selection made  
15 by the circuit CSC.

Step E3 and the following steps: the non-filtered codes are decoded by the decoder IDEC and executed by the units EU0-EU4.

Thus, the reading of a large instruction is  
20 done in two clock cycles as in the prior art, and comprises a cycle for preparing the addresses a0-a3 and a cycle for the reading of the codes. The codes read are reorganized and filtered during the read cycle. The operation is transparent for the operation of the  
25 entire processor. These steps are performed with overlapping, according to the standard rules of pipeline operation. For the sake of simplicity, the pipeline registers have not been described or shown.

Table 3 shown in the appendix is an integral  
30 part of the description and illustrates the operation of the processor for the reading of the instructions INST1 to INST4 described above. The parameters PC, R, R' and P0 that come into play in the execution of the algorithms are mentioned in the first columns. It is  
35 considered in this example that the codes of the instructions INST1 to INST3 are stored in the program memory PMEM1 from the address 0, and that the program



counter is equal to 0 at the beginning of the read process. The columns a0-a3 give the values of the addresses computed from the current value of the program counter PC. The columns c(0)-c(3) give the values of the codes read in the memory in the order in which they are. The columns c'(0) c'(3) give the values of the codes after reorganization by the circuit PCC. The last four columns c'(0)-c'(3) give the values of the codes after filtering in the circuit CSC.

If we observe the last four columns of Table 3, it can be seen that the codes therein are equivalent in arrangement and in value to the codes that were in the memory of the standard processor described in the introduction (see Table 1). Thus, the reading system according to the invention reconstitutes the NOP codes which, in the prior art, were recorded in the program memory.

In general, the making of the circuits IAC and CSC is within the scope of those skilled in the art, especially through techniques for the automatic designing of logic circuits using VHDL language. The algorithms A1 and A3 are expressed in VHDL language and the circuits IAC and CSC are automatically generated by a VHDL language compiler in the form of wired logic circuits. A non-restrictive description shall nevertheless be given, with reference to Figures 3 and 4, of exemplary embodiments of the circuits IAC and CSC in the case where the parameters I and N are equal to 4.

In Figure 3, the circuit IAC receives the value of a program counter PC at input. This value is encoded on 32 bits. The result R is obtained simply by separating the two LSB wires of the physical line conveying the value of the program counter PC, with R being equal to the two LSBs of the program counter. Similarly, P0 is equal to the 30 MSBs of the program counter and is obtained by separating the 30 MSB wires.

The parameter P0+1 is computed by an adder receiving the values P0 and 1 at input. The addresses a0-a3 are delivered by multiplexers MXA1-MXA3 receiving the parameters P0 and P0+1 at input. These multiplexers are driven by comparators CMP0-CMP3 receiving the index i at a first input and the parameter R at a second input.

In Figure 4, the circuit CSC is made by four multiplexers MXB0-MXB3 each receiving a code c'(j) at a first input and an NOP code at a second input. Each multiplexer is driven by a validation signal val0, val1, val2, val3 whose value determines the selection of the code c'(j) or the NOP code at output of the multiplexer. The validation codes are generated by a cascade of AND gates forming a daisy chain type of chain. Each AND gate receives, at input the validation signal for the previous code and the parallelism bit of the code received by the multiplexer to which it is related. Thus, the presence of a parallelism bit at 0 in a code c'(j) causes all the following validation signals to change over so that the concerned code and all the following codes are replaced by NOP codes.

The validation signal val(0) of the first code c'(0) is generated by an inverter gate because the parallelism bit of the first code, in principle, is always equal to 0 (/p). The multiplexer MUXB0 and the selection signal val0 of the first code c'(0) are, in principle, unnecessary since the first code c'(0) is, in principle, never filtered, and is a large instruction comprising at least one instruction code. However, the designing of this multiplexer is used to detect a possible defect in the reading of the program memory or a malfunction of the shift circuit PCC which appears when the parallelism bit of the first code c'(0) is different from 0. In this case, the validation signal val0 may be used as an error signal ERR.

The circuit CSC also comprises an adder ADD2 receiving the four validation signals val0 to val3 at

input. The output of this adder delivers the value  $n$  which is applied to the adder ADD1 for the incrementation of the program counter (Figure 2). The increment  $n$  is thus equal to the number of enabling signals equal to 1 and consequently represents the number of instruction codes that have not been filtered, namely the effective number of codes included in the large instruction that has just been read.

The present invention is, of course, open to several variations and embodiments. In particular, it is possible, in practice, to consider incorporating the filtering circuit CSC into the instruction decoder IDEC. Indeed, the function of this circuit is to ensure that codes not belonging to an instruction to be executed will not be sent to the execution units EU0-EU3. The filtering of the undesirable codes may thus be done downline from the instruction register IDEC by the decoder IDEC itself. In general, the positioning of the circuit CSC in the pipeline stages is dictated by the timing constraints relating to access to the memory PMEM1 and by the decoding times in the decoder IDEC, and come within the scope of those skilled in the art.

It will be clearly seen by those skilled in the art that the present invention provides a wide degree of liberty in the designing of a VLIW type processor. It is especially possible, as indicated above, to design a processor having a number  $I$  of memory banks and a number  $N$  of execution units where the number  $I$  is different from the number  $N$ . It is also possible to make a dynamic choice of the number  $N$  of active execution units, depending on the application planned, by inhibiting certain execution units to limit the current consumption. This inhibition of certain execution units may be designed to be programmable. The architecture of a processor according to the invention of this kind is not permanently fixed, like that of a standard VLIW processor. This is due to the

elimination of the obligation to read N instruction codes en bloc and the obligation resulting therefrom to inject NOP codes into a program when an instruction contains fewer than N codes. The present invention  
5 offers a wide range in the designing of a new type of processor reconciling the requirements of low consumption and compactness in terms of silicon surface area, and providing high performance characteristics through a high degree of parallelism.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25

**APPENDIX**

Reminders:

 $I = 4; N = 4$  $P0 = \text{Quotient } PC/I$ 5  $R = PC[\text{modulo } I]$  $R' = R$  of the previous clock cycle $a_i = P0+1$  if  $i < R$ , else  $a_i = P0$  $c'(j) = c(i)$ , with  $i=(j+R')[\text{modulo } I]$ 

TABLE 3: Reading of instructions INST1 to INST3 in memory banks M0 to M3

	(Addressing of banks M1-M3)				(Outputs of banks M1-M3)				(POC circuit outputs)				(CSC circuit outputs)							
Cycle	PC	R	R'	P0	a0	a1	a2	a3	c(0)	c(1)	c(2)	c(3)	c'(0)	c'(1)	c'(2)	c'(3)	c'(0)	c'(1)	c'(2)	c'(3)
1	0	0	-	0	0	0	0	0	-	-	-	-								
2	1	1	0	0	1	0	0	0	c0	c1	c2	c3	c0	c1	c2	c3	c0	NOP	NOP	NOP
3	3	3	1	0	1	1	1	0	c4	c1	c2	c3	c1	c2	c3	c4	c1	c2	NOP	NOP
4	7	3	3	1	2	2	2	1	c4	c5	c6	c3	c3	c4	c5	c6	c3	c4	c5	c6
5	8	0	3	2					c8	c9	...	c7	c7	c8	c9	...	c7	c8	c9	NOP